# HP PageWide Enterprise Color Flow MFP 785z+



### The new printing paradigm

Modern business demands forward-thinking technology – it's why HP engineered the next generation of HP PageWide Enterprise to deliver a competitive edge from every angle: lowest colour cost, 1 maximum uptime and the industry's strongest security.<sup>2</sup>





Get the quality you expect with HP PageWide Technology that delivers the

Print more pages and replace cartridges less often with optional high-yield

Print even faster – and save even more per page – by setting this printer to

Help keep energy costs down with the most efficient MFP in its class.<sup>5</sup>

Minimise interruptions with an HP PageWide device designed for the least

Print speeds up to 50% faster than competitors – as fast as 75 ppm in colour

Organise, staple, collate, and hole-punch with advanced external finishing that

Scan files directly to Microsoft® Office 365 and SharePoint, plus email, USB,

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. Learn more at: http://www.hp.com/go/learnaboutsupplies









# and network folders.<sup>8</sup> The world's most secure printing<sup>2</sup>

helps you ramp up production.

The lowest cost for colour<sup>1</sup>

General Office mode.<sup>4</sup>

maintenance in its class.<sup>6</sup>

and black-and-white.

lowest cost per colour page. 1

Minimal interruptions. Maximum uptime.

- Each printer in your fleet checks its operating code and repairs itself from attacks.
- Your printer's outgoing network connections are inspected to stop suspicious requests and thwart malware.
- Memory activity is monitored to continually detect and stop attacks.
- Firmware is automatically checked during startup to determine if it's authentic code – digitally signed by HP.

#### Give workgroups the speed they need

- Help workgroups capture every page easily and detect potential errors or missed pages – every time.
- Enter data more quickly and accurately using the pull-out keyboard.
- Help ensure every scanned document is properly oriented, cropped to size, and grayscale-optimized.
- Load up to 200 pages into the automatic document feeder for fast, unattended scanning.



2-sided printing

#### Product walkaround

#### HP PageWide Enterprise Color Flow MFP 785z+ shown

- 1. 20.3 cm (8.0 in) pivoting colour touchscreen
- 2. Hardware Integration Pocket
- 3. Easy-access USB printing port
- 4. Pull-out keyboard
- 5. Front door access to cartridges
- 6. 100 sheet multipurpose tray 1 supports media up to 305 x 457 mm (12 x 18 in)
- 7. 550 sheet tray 2 supports media up to 297  $\times$  432 mm (11.7  $\times$  17 in)
- 8. Optional  $3 \times 550$  sheet paper tray and stand supports media up to  $297 \times 432$  mm
- (11.7 x 17 in); One tray/stand accessory is required for the 785z+ model
- 9. 200 sheet ADF with single-pass, two-sided scanning with HP EveryPage  $\,$
- 10. Fax (standard)
- 11. Flatbed scanner handles up to 297 x 432 mm (11.7 x 17 in)
- 12. Upper bin of external finisher supports up to 250 sheets
- $13.\,\mbox{Lower}$  bin of external finisher supports up to 3,000 sheets; Staple, collate, and optional hole punch
- 14. Automatic two-sided printing
- 15. Host USB port, Ethernet network port, Hi-Speed USB 2.0 printing port



<sup>1</sup>The 785z+ is required to add one of the following accessories: 550 sheet Paper Tray and Cabinet, 3 x 550 sheet Paper Tray and Stand, 4,000 sheet HCI Paper Tray and Stand.

<sup>2</sup>The 350 sheet inner finisher is available on the HP PageWide Enterprise Color MFP 780dns and Flow MPF 785zs models only. Those models have a maximum output capacity of 850 sheets. The 3,250 sheets External Stapler Stacker (Z4L04A) is a required accessory for the Flow MFP 785z+ model. The z+ model has a maximum output capacity of 3,250 sheets. Models without the inner or external finisher have a maximum output capacity of 500 sheets.

## Accessories, Supplies and Support

Supplies	TOB23A HP 982A Cyan Original PageWide Cartridge (~8,000 pages)
	TOB26A HP 982A Black Original PageWide Cartridge (~10,000 pages)
	TOB24A HP 982A Magenta Original PageWide Cartridge (~8,000 pages)
	TOB25A HP 982A Yellow Original PageWide Cartridge (~8,000 pages)
	TOB27A HP 982X High Yield Cyan Original PageWide Cartridge (~16,000 pages)
	TOB30A HP 982X High Yield Black Original PageWide Cartridge (~20,000 pages)
	TOB28A HP 982X High Yield Magenta Original PageWide Cartridge (~16,000 pages)
	TOB29A HP 982X High Yield Yellow Original PageWide Cartridge (~16,000 pages)
Accessories	P1V18A HP PageWide 3x550 sheet Paper Tray and Stand
	W1B43A HP PageWide Printhead Wiper Kit
	P1V16A HP PageWide 550-sheet Paper Tray
	W1B45A HP PageWide Roller Kit
	W1B44A HP PageWide Service Fluid Container
	P1V17A HP PageWide 550-sheet Paper Tray and Cabinet
	P1V19A HP PageWide 4000 sheet High-capacity Paper Tray and Stand
	B5L28A HP Internal USB Ports
	B5L31A HP Foreign Interface Harness
	<b>E5K48A</b> HP 1 GB x32 144-pin (800 MHz)DDR3 SODIMM
	CC487A HP LaserJet MFP Analog Fax Accessory 500
	Z4L04A HP PageWide External Stapler Stacker
	Y1G11A HP LaserJet Hole Punch 2/4 Accessory
	Y1G12A HP LaserJet Hole Punch Swedish Accessory
	Y1G14A HP LaserJet Stapler/Stacker Finisher Staples
	J8030A HP Jetdirect 3000w NFC/Wireless Accessory
	J8031A HP Jetdirect 2900nw Print Server
Service and Support	U9RJ6E HP 3 year Next Business Day Service with Defective Media Retention for PageWide Colour 78x U9RJ7E HP 4 year Next Business Day Service with Defective Media Retention for PageWide Colour 78x U9RJ8E HP 5 year Next Business Day Service with Defective Media Retention for PageWide Colour 78x U9RK5PE HP 1 year Post Warranty Next Business Day Service with Defective Media Retention for PageWide Colour 78x U9RK6PE HP 2 year Post Warranty Next Business Day Service with Defective Media Retention for PageWide Colour 78x

# **Technical specifications**

Model	HP PageWide Enterprise Color Flow MFP 785z+	
Product number	Z5G75A	
Functions	Print, copy, scan, fax	
Control panel	20.3 cm (8.0 in) Colour Graphics Display (CGD) with touchscreen; Rotating (adjustable angle) display; Illuminated Home button (for quick return to the Home menu); USB High-speed 2.0 port; Hardware Integration Pocket	
Print		
Print technology	HP PageWide Technology	
Print speed <sup>1</sup>	Black (A4, normal) Up to 55 ppm; Colour (A4, normal): Up to 55 ppm; Black (A4, duplex): Up to 38 ppm; Colour (A4, duplex): Up to 38 ppm; Black (General Office): Up to 75 ppm; Colour (General Office): Up to 75 ppm;	
First page out <sup>2</sup>	Black (A4, ready): As fast as 7.0 sec; Colour (A4, ready): As fast as 7.0 sec; Black (A4, sleep): As fast as 17.5 sec; Colour (A4, sleep): As fast as 17.5 sec;	
Print resolution	Black (best): Up to 1200 x 1200 optimised dpi from 600 x 600 input dpi (on Unspecified, Plain, HP Premium Presentation Matte, and HP Brochure Matte); Colour (best): Up to 2400 x 1200 optimised dpi from 600 x 600 input dpi (on HP Advanced Photo Papers); Technology: HP PageWide Technology up to 1200 x 1200 optimised dpi from 600 x 600 input dpi;	
Monthly duty cycle	Up to 125,000 pages A4; Recommended monthly page volume: 2,500 to 25,000	
Printer smart software features	HP SureStart; Run-time Intrusion detection; Whitelisting; HP Trusted Platform Module; HP JetAdvantage Security Manager; HP Web Jetadmin; Open Extensibility Platform; FutureSmart Firmware; HP ePrint; Apple AirPrint <sup>TM</sup> ; HP Auto-On/Auto-Off technology; HP Colour Access Control; HP EasyColour; Front-facing USB printing; Store print jobs; Print preview; Automatic two-sided printing; Print multiple pages per sheet (2, 4, 6, 9, 16); Collation; Booklet printing; Cover pages; Tray selection; Scaling; Portrait/Jandscape orientation; High Quality Grayscale and Black Ink Only; General Office/Professional/Presentation dpi print modes; Optional: HP and third party extensibility solutions; Wireless	
Standard print languages	HP PCL 6; HP PCL 5c; HP postscript level 3 emulation; PDF 1.7	
Fonts and typefaces	105 internal TrueType fonts scalable in HP PCL; 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); Additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at http://www.hp.com/go/laserjetfonts	
Print area	Print margins Top: 4.23 mm (Default), 2 mm (Edge-to-Edge mode), Bottom: 4.23 mm (Default), 2 mm (Edge-to-Edge mode), Left: 4.23 mm (Default), 2 mm (Edge-to-Edge mode), Right: 4.23 mm (Default), 2 mm (Edge-to-Edge mode);	
Print cartridges number	4 (1 each black, cyan, magenta, yellow)	
Multitasking supported	Yes	
Memory card compatibility	144-pin DDR3 DIMM	
Duplex printing	Automatic (standard)	
Сору	Displaced ICO) the tenting of the ICO the I	
Copy speed	Black (A4, ISO): Up to 55 cpm; Colour (A4, ISO): Up to 55 cpm  Two-sided copying, scalability, image adjustments (darkness, contrast, background cleanup, sharpness), N-up, N or Z-ordering, content orientation, collation, booklet, ID	
Copier specifications	Scan, job build, edge-to-edge, job storage; Maximum number of copies: Up to 9999 copies; Copy resolution: Up to 600 x 600 dpi; Reduce/Enlarge: 25 to 400%;	
Copier smart software features	Auto scale; Reduce/enlarge from scanner glass (25 to 400 percent); Collate; Auto colour detection; Two-sided copying; Image adjustments (darkness, background cleanup, sharpness); Job build	
Scan		
Scan speed	Normal (A4): Up to 120 ipm simplex and up to 240 ipm duplex; Duplex (A4): Up to 120 ipm simplex and up to 240 ipm duplex	
Scan file format	Digital Send: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF/A (OCR), HTML (OCR), CSV (OCR); Scan to easy access USB: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF/A (OCR), HTML (OCR), CSV (OCR); Print from easy access USB: PDF, PS, Print Ready files (.prn, .pcl, .cht)	
Scanner specifications	Scanner type Flatbed, ADF; Scan technology: Charge Coupled Device (CCD) & Contact Image Sensor (CIS); Scan input modes: Front panel applications: Copy; E-mail; Fax; Save to Network Folder; Save to USB; Save to Device Memory; Save to SharePoint; Open Extensibility Platform (OXP) applications; Twain version: Version 2.1; Duplex ADF scanning: Yes, single-pass duplexing ADF; Scan size maximum (flatbed, ADF): 297 x 432 mm; Optical scan resolution: Up to 600 ppi	
Scanner advanced features	Optimise text/picture; Image adjustments; Job build; Output quality setting; Selectable scan resolution 75 to 600 dpi; Auto detect colour; Edge erase; Job notification; Blank page suppression; HP Quick Sets; HP EveryPage; Auto orientation; Embedded Optical Character Recognition (OCR), Auto crop to page; Auto-tone	
Recommended monthly scan volume	2,000 to 75,000	
Scannable area	Maximum media size (flatbed): 297 x 432 mm; Minimum media size (ADF): 68 x 148 mm Maximum media size (ADF): 297 x 432 mm; Up to 297 x 1000 mm when "long scan size" selected	
Bit depth/ Grey scale levels	24-bit / 256	
Digital sending	Standard: Scan to E-mail; Save-to-Network Folder; Save-to-USB drive; Send to FTP; Send to LAN Fax; Send to Internet Fax; Local Address Book; SMTP over SSL; Blank Page Removal; Edge Erase; Auto Colour Sense; Auto Crop To Content; Compact PDF	
Fax		
Fax <sup>3</sup>	Optional, 33.6 kbps	
Fax specifications	Fax memory: Up to 500 pages; Fax resolution: Standard: 204 x 98 dpi; Fine: 204 x 196 dpi; Quick dialing: Up to 1000 numbers (each with 210 destinations); Telecom compliance: ES 203 021-1 v2.1.1; ES 203 021-2 v2.1.2; ES 203 021-3 v2.1.2	
Fax smart software features	Stored faxes; Fax archiving; Fax forwarding; Scale to fit; Fax address book; LAN/Internet fax; Fax number confirmation; Holiday fax schedule	
Processor speed	1.2 GHz	
Connectivity Standard	2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000TX network; 1 Wireless 802.11b/g/n; 1 Bluetooth Low Energy; 1 RJ-11 modem port/phone line	
Optional	HP Jetdirect 3000w NFC/Wireless Accessory J8030A, HP Jetdirect 2900nw Print Server J8031A	
Wireless	Yes, built-in Wi-Fi 802.11b/g/n	
Mobile printing capability	HP ePrint, Apple AirPrint™, Google Cloud Print	
Supported network protocols	IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print	
-		
Network capabilities	Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPsec (standard)	

Memory   Standard: 5632 MB; Maximum: 5632 MB; MB; Maximum: 5632	P 785z+		
Memory   Standard: 5632 MB; Maximum: 5632 MB; MB; Maximum: 5632			
Paper handling	320 GB High-Performance Secure Hard Disk (AES 256 hardware encryption or greater; Secure erase capabilities: Secure File Erase-Temporary Job Files, Secure Erase Job Data, Secure ATA Erase-Disk)		
Standard: 2 (additional required purch or HP PageWide 4,000-sheet HCI Page	МВ		
Media types  Plain paper, HP EcoFFICIENT, HP Premit Intermediate 85-95g, Mid-Weight 96-1 Prepunched, Coloured, Bond, Recycted  Custom (metric): Tray 1: 99.1 x 127 to Supported (metric): Tray 1: 99.1 x 127 to Supported (metric): Tray 1: 99.1 x 127 to Supported (metric): Tray 1: 199.1 x 127 to Standard output: 3,000 sheet lower bit Optional input: 1 x 550/stand (a/3/Aq); ADF: Standard output: 3,000 sheet lower bit Optional input: 1 x 550/stand (a/3/Aq); ADF: Standard, 2,000 sheets  Media weight  Tray: 1: 60-220 g/m², 300 g/m² Photo.  Input capacity  Maximum: Up to 4,650 sheets  ADF: Standard: Up to 3,000 sheets (80 g/m² Maximum: Up to 3,250 sheets (80 g/m² Maximum: Up to 3,250 sheets (80 g/m² Maximum: Up to 3,250 sheets (80 g/m² Android, Linux Boss (5.0), Linux Debian 17.3, 18), Linux Red Hat Enterprise (6.1 Capitan, 05 X 10.10 Vosemite, UNIX, we ditions (excluding RT 05 for Tablets), etc.)  Compatible operating systems  Compatible network operating systems  Printa (spilanting network)  Minimum system requirements  Minimum system requirements  Minimum system req			
Intermediate 85-95g, Mid-Weight 96-1   Prepunched, Coloured, Bond, Recycled	Standard: 2 (additional required purchase of the HP PageWide 550-sheet Paper Tray and Stand W1B50A, HP PageWide 3 x 550-sheet Paper Tray and Stand W1B51A or HP PageWide 4,000-sheet HCl Paper Tray and Stand W1B52A); Maximum:		
Media size  Supported (metric): Tray 1: RA3, A3, B8 A4R., 16K, 16KR., A5, A5, RB, SUIS, IS, ADF: A3, Ledger, B4-JIS, A4, B5-JIS, A5, B4-R. 16K, 16KR., A5, A5-R, B5 UIS, A5, ADF: A3, Ledger, B4-JIS, A4, B5-JIS, A5, ADF: Standard output: 3,000 sheet lower bin Optional Input: 1 x 550/stand (A3/A4); ADF: Standard, 200 sheets  Media weight  Tray 1: 60-220 g/m², 300 g/m² Photo  Input capacity  Maximum: Up to 4,650 sheets  ADF: Standard; 200 sheets  ADF: Standard; 200 sheets  Standard: Up to 3,000 sheets (800 g/m² Maximum: Up to 3,250 sheets (800 g/m² Maximum: Server 2008 R2 Ferminal Services), Windows Server 2008 R2 Ferminal Services, W	Plain paper, HP EcoFFICIENT, HP Premium Presentation Matte 120g, HP Brochure Matte 180g, HP Brochure Glossy, HP Advanced Photo Papers, Light 60-74g, Intermediate 85-95g, Mid-Weight 96-110g, Heavy 111-130g, Extra Heavy 131-175g, Cardstock 176-220g, Labels, Letterhead, Envelope, Heavy Envelope, Preprinted Prepunched, Coloured, Bond, Recycled, Rough		
Media handling   Standard output: 3,000 sheet tower bir Optional input: 1 x 550 (Stand (A3/A4); ADF: Standard, 200 sheets	Custom (metric): Tray 1: 99.1 x 127 to 304.8 x 457.2 mm; Tray 2-5: 210.1 x 148.1 to 297.2 x 431.8 mm; HCI Trays 3 & 4: A4 Supported (metric): Tray 1: RA3, A3, 8K, B4 (JIS), SRA4, RA4, A4, A4-R, 16K, 16K-R, A5, A5-R, B5 (JIS), B5 (JIS)-R, B6 (JIS), A6; Trays 2-5: A3, 8K, B4 (JIS), SRA4, RA4, A4-R, 16K, 16K-R, A5, A5-R, B5 (JIS), A6; Trays 2-5: A3, 8K, B4 (JIS), SRA4, RA4, A4-R, 16K, 16K-R, A5, A5-R, B5 (JIS), A6; Trays 3-4: A4 ADF: A3, Ledger, B4-JIS, A4, B5-JIS, A5, B6-JIS, A6		
Input capacity  Maximum: Up to 4,650 sheets ADF: Standard, 200 sheets  Standard: Up to 3,000 sheets (80 g/m² Maximum: Up to 3,250 sheets (80 g/m² Maximum: Up to 1,250 sheets (80 g/m² Maximum: Up to 3,250 sheets (80 g/m² Maximum: Up t	Standard input: 100-sheet multipurpose tray, 550-sheet input tray Standard output: 3,000 sheet lower bin Optional input: 1 x 550/stand (A3/A4); 3 x 550/stand (A3/A4); HCl (2 x 2,000 sheet A4) ADF: Standard, 200 sheets		
Output capacity  ADF: Standard, 200 sheets  Standard: Up to 3,000 sheets (80 g/m² Maximum: Up to 3,250 sheets (80 g/m² Maximum: Up to 3,250 sheets (80 g/m² Maximum: Up to 3,250 sheets (80 g/m² Android, Linux Boss (5.0), Linux Debian 17.3, 18), Linux Red Hat Enterprise (6.6 Capitan, 05 X 10.10 Yosemite, UNIX, Weditions (excluding RT OS for Tablets), veditions (excluding RT OS for Windows Server 2008 RZ SP1 Terminal Services), Windows Server 2008 RZ SP1 Terminal Services), Windows Server 2008 RZ SP1 Terminal Services, Windows Server 2008 RZ SP1 Terminal Server 2008 RZ SP1 Terminal Server	Tray 1: 60-220 g/m², 300 g/m² Photo Paper Only; Trays 2-5: 60-220 g/m²; HCl trays 3-4: 60-220 g/m²		
Compatible operating systems  Compatible network operation systems  Compatible network operating systems  Compatible network operation systems  Comp			
Compatible operating systems			
Compatible network operating systems  Compatible network of systems  Compatible networ	Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS mac, OS 10.12 Sierra, OS X 10.11 El Capitan, OS X 10.10 Yosemite, UNIX, Windows 10 all 32/64-bit editions (excluding RT OS for Tablets), Windows 7 all 32/64-bit editions (excluding RT OS for Tablets), Windows Vista all 32-bit editions (Home Basic, Premium, Professional, etc.), Windows XP SP3 32-bit editions (XP Home, XP Pro, etc.)		
Security management  Security management  Mac: 1.3 GB available hard drive space;  HP Connected, HP Device Experience (I or OS App Source for printer software),  Identity Management: Kerberos author readers); Network: IPsec/firewall with (EAP-PEAP, EAP-TLS), SNMPV3, HTTPS, Email (uses FIPS 140 validated cryptog disablement, Hardware Integration Por attacks), HP Sure Start Secure Boot (Bli Management: Compatible with HP Jeth Management: Compatible with HP Jeth more security settings go to http://h1c  Printer management  Printer dimensions (W x D x H)  Package dimensions (W x D x H)  Package dimensions (W x D x H)  Printer weight  171.0 kg  Package weight  Operating environment  Temperature: 15 to 30°C Humidity: 30 to 70% RH  Temperature: Before initial setup (nonmust slowly warm up to an approved of Humidity: 10 to 80% RH  Power <sup>4</sup> Power <sup>4</sup> Requirements: Input voltage: 100 to 22 Consumption: 740 watts (max, printing Typical Electricity Consumption (TEC) <sup>5</sup> :	3.0, Citrix MetaFrame XP Presentation Server (Feature Release 1, 2, and 3), Citrix on Windows Server 2003/2003 R2, Citrix on R2 SP1, Citrix on Windows Server 2012/2012 R2, Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus Feature Pack 2 & 3) vices 32/64-bit, Citrix XenApp 6.0/6.5 (for Windows Server 2008 R2 Terminal Services, 32/64-bit), Citrix XenApp 6.0/6.5/7.5 (for Libervices, 32/64-bit), Citrix XenApp 7.5 (for Windows Server 2012 and 2012 R2 Terminal Services, 64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix YenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix YenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services), Windows Novell Cleints http://www.novell.com/iprint, Novell reprise Server 11/SP1, Novell Open Enterprise Server 2 for Linux, Novell Servers http://www.novell.com/iprint), Windows Server andard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2008 32/64-bit (SP1/SP2) windows Server 2008 32/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2008 42/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2016/64-bit ster & Terminal Services), Windows Server 2016/64-bit ster & Terminal Services)		
or OS App Source for printer's oftware),  Identity Management: Kerberos auther readers); Network: IPsec/firewall with (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, Email (uses FIPS 140 validated cryptog disablement, Hardware Integration Por attacks), HP Sure Start Secure Boot (Bl Management: Compatible with HP JetA more security settings go to http://h1c  Printer management  Printer dimensions and weight  Printer dimensions (W x D x H)  Package dimensions (W x D x H)  Package dimensions (W x D x H)  Package weight  171.0 kg  Package weight  109.4 kg  Temperature: 15 to 30°C Humidity: 30 to 70% RH  Temperature: Before initial setup (nonmust slowly warm up to an approved of Humidity: 10 to 80% RH  Power <sup>4</sup> Power <sup>4</sup> Requirements: Input voltage: 100 to 24 Consumption: 740 watts (max, printing Typicial Electricity Consumption (TEC) <sup>5</sup> :	ce; OS hardware requirements see http://www.microsoft.com Internet; OS hardware requirements see http://www.Apple.com for more info		
readers); Network: IPsec/firewall with to (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, Email (uses FIPS 140 validated cryptog disablement, Hardware Integration Por attacks), HP Sure Start Secure Boot (Bl Management: Compatible with HP JetA more security settings go to http://h1c  Printer management	DXP), HP PCL 6 Printer Driver, HP Software Installer/Uninstaller, Mac OS Welcome Screen (Directs users to http://www.123.HP.com online user manuals		
Printer management  Print Driver  Dimensions and weight  Printer dimensions (W x D x H)  Package dimensions (W x D x H)  Printer weight  Package weight  Operating environment  Temperature: 15 to 30°C Humidity: 30 to 70% RH  Temperature: Before initial setup (non-must slowly warm up to an approved of Humidity: 10 to 80% RH  Power <sup>4</sup> Power <sup>4</sup> Power <sup>4</sup> Printer Driver  Minimum 1245 x 693 x 1222 mm; Maximum: 2495 x 1175 x 1535 mm (w 790 x 760 x 1027 mm 790 x 102	Identity Management: Kerberos authentication, LDAP authentication, 1000 user PIN codes, optional HP and third-party advanced authentication solutions (e.g., badge readers); Network: IPsec/firewall with Certificate, Pre-Shared Key, and Kerberos authentication, Supports WJA-10 IPsec configuration Plug in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control List, HP Trusted Platform Module (TPM) comes standard; Data: Storage Encryption, Encrypted PDF & Email (uses FIPS 140 sulfateded cryptographic libraries from Microsoft), Secure Fass, SSL/TLS (HTTPS), Encrypted Credentials; Device: Security lock slot, USB port disablement, Hardware Integration Pocket for security solutions, 18 Intrusion Detection with Red Balloon Security Technology (Constant in-device monitoring for attacks), HP Sure Start Secure Boot (BIOS integrity checking with self-healing capability), Whitelisting (loads only known good code (DLLs, EXEs, etc.); Security Management: Compatible with HP JetAdvantage Security Manager, 21 Device Security Syslog Messages processed and accessible in ArcSight and Splunk SIEMs; For more security settings go to http://h10032.www1.hp.com/ctg/Manual/c03602120		
Printer dimensions (W x D x H)  Package dimensions (W x D x H)  Printer weight  Package weight  Operating environment  Storage conditions  Minimum 1245 x 693 x 1222 mm; Maximum: 2495 x 1175 x 1535 mm (w 790 x 760 x 1027 mm  171.0 kg  109.4 kg  Temperature: 15 to 30°C Humidity: 30 to 70% RH  Temperature: Before initial setup (nonmust slowly warm up to an approved of Humidity: 10 to 80% RH  Power <sup>4</sup> Requirements: Input voltage: 100 to 22 Consumption: 740 watts (max. printing Typical Electricity Consumption (TEC) <sup>5</sup> :	SNMP Proxy Agent; HP Web JetAdmin Software; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal		
Package dimensions (W x D x H)  Package dimensions (W x D x H)  Printer weight  Package weight  171.0 kg  Package weight  109.4 kg  Operating environment  Temperature: 15 to 30°C Humidity: 30 to 70% RH  Temperature: Before initial setup (non-must slowly warm up to an approved of Humidity: 10 to 80% RH  Power <sup>4</sup> Requirements: Input voltage: 100 to 24 Consumption: 740 watts (max. printing Typical Electricity Consumption (TEC) <sup>5</sup> :			
Printer weight 171.0 kg Package weight 109.4 kg  Operating environment Temperature: 15 to 30°C Humidity: 30 to 70% RH  Temperature: Before initial setup (nonmust slowly warm up to an approved of Humidity: 10 to 80% RH  Power <sup>4</sup> Requirements: Input voltage: 100 to 2 <sup>c</sup> Consumption: 740 watts (max. printing Typical Electricity Consumption (TEC) <sup>5</sup> :	vith all doors and trays open, and document feeder lifted);		
Package weight 109.4 kg  Operating environment Temperature: 15 to 30°C Humidity: 30 to 70% RH  Temperature: Before initial setup (nonmust slowly warm up to an approved of Humidity: 10 to 80% RH  Power4 Requirements: Input voltage: 100 to 24 Consumption: 740 watts (max. printing Typical Electricity Consumption (TEC) <sup>5</sup> :	790 x 760 x 1027 mm		
Operating environment  Temperature: 15 to 30°C Humidity: 30 to 70% RH  Temperature: Before initial setup (nonmust slowly warm up to an approved of Humidity: 10 to 80% RH  Requirements: Input voltage: 100 to 20 Consumption: 740 watts (max. printing Typical Electricity Consumption (TEC) <sup>5</sup> :	171.0 kg		
Humidity: 30 to 70% RH  Temperature: Before initial setup (non- must slowly warm up to an approved or Humidity: 10 to 80% RH  Requirements: Input voltage: 100 to 2 Consumption: 740 watts (max. printing Typical Electricity Consumption (TEC) <sup>5</sup> :	109.4 kg		
Storage conditions must slowly warm up to an approved or Humidity: 10 to 80% RH  Requirements: Input voltage: 100 to 2c Consumption: 740 watts (max. printing Typical Electricity Consumption (TEC) <sup>5</sup> :			
Power <sup>4</sup> Consumption: 740 watts (max. printing Typical Electricity Consumption (TEC) <sup>5</sup> :	Temperature: Before initial setup (non-purged): -40 to 60°C; After initial setup (purged): 0 to 60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). Humidity: 10 to 80% RH		
	Requirements: Input voltage: 100 to 240 VAC, 50/60 Hz; Consumption: 740 watts (max. printing), 570 watts (printing), 50 watts (ready), 1.3 watts (sleep), 0.2 watts (auto-off), 0.2 watts (off); Typical Electricity Consumption (TEC) <sup>5</sup> : Blue Angel: 4.287 kWh/Week; Energy Star: 4.009 kWh/Week; Power supply type: Internal (Built-in) power supply;		
Energy savings feature technology HP Auto-on/Auto-off Technology			

Model	HP PageWide Enterprise Color Flow MFP 785z+	
Product number	ZSG75A	
Certifications	CISPR 22:2008 Class A, CISPR 32:2012 Class A, EN 55032:2012 Class A, EN 61000-3-3:2013, EN 61000-3-2:2014 ENERGY STAR® qualified; EPEAT® Silver <b>Blue Angel compliant</b> Yes, Blue Angel DE-UZ 205	
Country of origin	Made in Netherlands	
What's in the box	HP PageWide Enterprise Color Flow MFP 785z+; HP Setup Ink Cartridges (yield after setup 8,000 pages CMY and 10,000 Black); Installation guide; Support flyer; Documentation on CD-ROM; Power cord	
Warranty	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to http://www.hp.com/support to learn about HP award winning service and support options in your region.	

#### **Footnotes**

- ¹ Lowest cost per colour page claim applies to devices that are not sold under contract: Comparison of HP PageWide A3 devices with the majority of in-class colour ink/laser MFPs (€2,820-€7,049) and colour ink/laser single function printers (€1,410-€2,819) as of January/February 2017; market share as reported by IDC as of Q4 2016. Cost per page (CPP) reported by gap intelligence Pricing & Promotions Report January/February 2017; comparisons for devices/supplies not sold under contract are based on published specifications of the manufacturers' highest-capacity cartridges, inclusive of long life consumables and page yield. Average HP yield based on ISO/IEC 24711 and continuous printing in default mode. Actual yield varies based on content of printed pages and other factors. For more information, see http://www.hp.com/go/learnaboutsupplies and hp.com/go/PageWideClaims.
- <sup>2</sup> Based on HP review of 2018 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit http://www.hp.com/go/PrintersThatProtect. For more information: http://www.hp.com/go/printersecurityclaims.
- <sup>3</sup> High-yield cartridges are not included in printer purchase; purchase separately. Learn more at http://www.hp.com/go/learnaboutsupplies.
- <sup>4</sup> Comparison based on printing in Professional Mode.
- <sup>5</sup> Energy claim based on TEC data reported on energystar.gov as of February 2018. Data normalised to determine energy efficiency of in-class colour laser printers and MFPs with print speeds between 20-80 ppm as of February 2018. Subject to device settings. Actual results may vary.
- <sup>6</sup> Fewer service parts claim based on BLI analysis of leading in-class A3 MFPs as of August 2016; calculations use publicly available and/or published manufacturer rated yields for long-life consumables and assume 600,000 pages printed (using a 60% black/40% colour ratio); market share as reported by IDC as of Q3 2016. Learn more at http://www.hp.com/qo/learnaboutsupplies.
- 7 Comparison of HP PageWide A3 devices with the majority of in-class colour ink/laser MFPs (€2,820-€7,049) and colour ink/laser single function printers (€1,410-€2,819) as of April 2017; market share as reported by IDC as of Q4 2016, excluding other HP PageWide products. HP PageWide speeds based on General Office mode and exclude first page. Learn more at http://www.HP.com/go/printerspeeds.
- <sup>8</sup> Requires an Internet connection to the printer. Services may require registration. App availability varies by country, language, and agreements. For details, see http://www.hpconnected.com
- 9 Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

#### Technical specifications disclaimers

- 1 ISO speeds measured using ISO/IEC 24734. Excludes first page or first set of ISO test pages. For details see http://www.hp.com/go/printerclaims.
- <sup>2</sup> Exact speed varies depending on the system configuration, software application, driver and document complexity.
- <sup>3</sup> Based on standard ITU-T test image at standard resolution and MMR encoding, the HP fax device can transmit at 3 sec/page for V.34 and 6 sec/page for V.17.
- <sup>4</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power Consumption and Energy Star TEC values typically based on measurement of 115V device.
- <sup>5</sup> Normalized TEC (watt hours per page) Blue Angel: 0.257 Wh/page, Energy Star: 0.269 Wh/page.

















#### http://www.hp.com/uk

The product could differ from the images shown. © Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



