



Lexmark MS911de

High-volume output, long-life components, solid security and advanced finishing make the Lexmark MS911de the ultimate SRA3-capable monochrome printer from Lexmark.

Part Number	Novell Operating Systems Supported	Optional Local Ports
26Z0035	Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server	Internal RS-232C serial, Internal 1284-B Bidirectional Parallel
Print Technology	UNIX Operating Systems Supported	Optional Network Ports
Monochrome Laser	HP-UX 11.11, 11.23, 11.31, Sun Solaris SPARC 9, 10, 11, Sun Solaris x86 10, 11, IBM AIX 5.3, 6.1, 7.1	Internal MarkNet N8350 802.11b/g/n Wireless
Function	Included Paper Handling	Direct USB
Printing	250-Sheet Output Bin, 150-Sheet Multipurpose Feeder, 2 x 500-Sheet Input	Yes
Workgroup Size	Optional Paper Handling	Ethernet Network
Departmental Workgroup	Staple Punch Finisher, Inline Stapler, 2500-Sheet Tandem Tray, 3000-Sheet Tray, Booklet Finisher, 2 x 500-Sheet Tray	Yes
Touch Screen Display	Paper Input Capacity, Standard	Network Protocol Support
Yes	Up to 1150 pages 75 gsm bond	TCP/IP IPv4, AppleTalk™, TCP/IP IPv6, TCP, UDP
Display	Paper Input Capacity, Maximum	Network Printing Methods
Lexmark e-Task 4.3-inch (10.9 cm) colour touch screen	Up to 6650 pages 75 gsm bond	LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing
Print Speed (A4, Black)	Paper Output Capacity, Standard	Network Management Protocols ¹
Up to 55 ppm ⁶	Up to 250 pages 75 gsm bond	HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Telnet, Finger,
Print Speed (A4, Black) Duplex	Paper Output Capacity, Maximum	Network Security
Up to 55 ppm ⁶	Up to 3500 pages 75 gsm bond	SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec
Time to First Page (Black)	Paper Weight Range Supported - Standard	Printable Area (metric)
As fast as < 5.5 seconds	Tray (gsm) 60 - 256 gsm	4.2, 3, 3, 3 mm of the top, bottom, right and left edges (within)
Duplex (2-sided) Printing	Paper Weight Range Supported - Multipurpose Feeder (gsm)	Printer Languages (Standard)
Integrated Duplex	60 - 256 gsm	PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, Microsoft XPS (XML Paper Specification), AirPrint™, PDF 1.7 emulation
Print Resolution, Black	A3	Fonts and Symbol Sets
1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 600 x 600 dpi	Yes	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 158 scalable PostScript fonts, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.
Processor	Finishing Option	Laser Cartridge Yields (up to)⁵
Dual Core, 800 MHz	Yes	, 32,500-page High Yield Cartridge
Memory, Standard	Finishing Functions	Photoconductor Estimated Yield
512 MB	Offset stacking, Stapling, Hole punching, Booklet fold and saddle stapling	Up to 125,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage ⁴
Memory, Maximum	Number of Paper Inputs, Standard	Cartridge(s) Shipping with Product
2560 MB	3	21,000-page Starter Toner Cartridge
Hard Disk	Number of Paper Inputs, Maximum	Packaged Size (mm - H x W x D)
Option available	6	965 x 762 x 838 mm
Apple Operating Systems Supported	Media Types Supported	Packaged Weight, kg
Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10)	Card Stock, Envelopes, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide.	90 kg
Linux Operating Systems Supported	Media Sizes Supported	Size (mm - H x W x D)
SUSE Linux Enterprise Server 10, 11, SUSE Linux Enterprise Desktop 10, 11, Red Flag Linux Desktop 6.0, Linpus Linux Desktop 9.6, Debian GNU/Linux 5.0, 6.0, Red Hat Enterprise Linux WS 4.0, 5.0, 6.0, PCLinuxOS 2011, Mint 10, 11, 12, 13, openSUSE 11.4, 12.1, 12.2, Ubuntu 12.04, 12.10, Fedora 17, 18, 19	10 Envelope, 7 3/4 Envelope, 9 Envelope, A3, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Universal, Super Tabloid (12 x 18"), Oficio, A6, SRA3	770 x 615 x 697 mm
Microsoft Windows Operating Systems Supported	Standard Ports	
Windows XP, Windows Server 2003, Windows XP x64, Windows Server 2003 x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1, Windows 10	One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A)	

Weight

74 kg

Size, Trays Extended (mm - H x W x D)

762 x 953 x 1127 mm

Noise Level, Idle

28 dBA

Noise Level (Print), Operating

54 dBA

Duplex Print Noise Level, Operating

55 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.5 watts

Average Power (Sleep Mode)

2.5 watts

Average Power (Ready Mode)

190 watts

Average Power (Printing)

910 watts

Average Power while Printing Duplex

830 watts

ENERGY STAR Typical Electricity**Consumption (TEC)**

3.9 kilowatt-hours per week

Product Warranty

1-Year Base Warranty Service

Product Certifications

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, cTUV, US FDA/CDRH, cTUVus, IEC 60825-1, CB Report, NCC Mark, FCC, CE (EU) DoC, EFTA (CE), KCC, RCM, CCC, C-tick DoC, EuP, CECP, CEL, ECMA-370, TED, GOST-R, SII, TER, Bel GISS, SABS, TUV-AR, KC mark, BIS, TUV-GS Mark

Maximum Monthly Duty Cycle

Up to 300,000 pages per month³

Recommended Monthly Page Volume

15,000 - 59,000 pages²

Specified Operating Environment

Altitude: 0 - 2500 Meters (8,200 Feet),

Humidity: 15 to 85% Relative Humidity,

Temperature: 10 to 30°C (50 to 86°F)

Country of Origin

China (PRC)

UNSPSC Code

43212105

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)


²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average standard page yield value declared in accordance with ISO/IEC 19752.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



P/N **Toner Cartridges**

25A0013	Staple Cartridges (3 pack)	2357022	MS911 Install, De-Install Service
54G0P00	Photoconductor Unit		
54G0W00	Waste Toner Bottle		
54G0H00	MS911 High Yield Toner Cartridge		

P/N **Paper Handling**

26Z0087	2500-Sheet Tandem Tray (A4)	40X9669	300K Maintenance Kit
26Z0089	3000-Sheet Tray (A4)	40X9046	Fuser
26Z0085	2 x 500-Sheet Tray	40X9936	Developer unit
26Z0084	MS911, MX910, MX911 Inline Stapler		
26Z0091	MS911, MX91x Banner Media Tray		
26Z0082	MS911, MX91x Booklet Finisher (4-Hole)		
26Z0080	MS911, MX91x Staple Punch Finisher (4-Hole)		

P/N **Furniture**

26Z0094	Cabinet with casters
---------	----------------------

P/N **Memory Options**

27X0200	320+ GB Hard Disk
57X9016	1024MBx32 DDR3-DRAM
57X9012	2048MBx32 DDR3-DRAM
57X9101	256MB Flash Memory Card

P/N **Application Solutions**

26Z0024	MS911 Card for IPDS
26Z0023	MS911 Forms and Bar Code Card
26Z0025	MS911 Card for PRESCRIBE Emulation

P/N **Connectivity**

27X0142	Lexmark MarkNet™ N8230 Fiber Ethernet Print Server
1021231	Parallel (10') Cable
1021294	USB (2 Meter) Cable
14F0100	RS-232C Serial Interface Card
14F0000	Parallel 1284-B Interface Card
27X0225	MarkNet N8350 802.11b/g/n Wireless Print Server
57X7000	English Keyboard Kit
27X0310	MarkNet N8350 Wireless Print Server plus NFC
SPD0002	Surge Protective Device, 220-240V

P/N **Extended Warranties**

2356940	MS911 1-Year Onsite Service
2356941	MS911 2-Year Onsite Service
2356942	MS911 3-Year Onsite Service
2356943	MS911 4-Year Onsite Service
2356944	MS911 1-Year Onsite Service Renewal